







BELIBAL216



*\*6 pcs. shown for shade variation\** - 2x16 -

BELIBALJOLLY



- .5x8 jolly -



BELIBAQ216



*\*6 pcs. shown for shade variation\** - 2x16 -

BELIBAQJOLLY



- .5x8 jolly -






*ibiza*  
**BLACK**

BELIBBK216



\*6 pcs. shown for shade variation\* - 2x16 -

BELIBBKJOLLY



- .5x8 jolly -




*ibiza*  
**DARK PEARL**

BELIBDP216



\*6 pcs. shown for shade variation\* - 2x16 -

BELIBDPJOLLY



- .5x8 jolly -






*ibiza*  
**GINGER**

BELIBGI216



\*6 pcs. shown for shade variation\* - 2x16 -

BELIBGIJOLLY



- .5x8 jolly -



*ibiza*  
**GREEN**

BELIBGN216



\*6 pcs. shown for shade variation\* - 2x16 -

BELIBGNJOLLY



- .5x8 jolly -






BELIBHE216



\*6 pcs. shown for shade variation\* - 2x16 -

BELIBHEJOLLY



- .5x8 jolly -



BELIBMO216



\*6 pcs. shown for shade variation\* - 2x16 -

BELIBMOJOLLY



- .5x8 jolly -






BELIBPI216



\*6 pcs. shown for shade variation\* - 2x16 -

BELIBPIJOLLY



- .5x8 jolly -



BELIBWH216



\*6 pcs. shown for shade variation\* - 2x16 -

BELIBWHJOLLY



- .5x8 jolly -

# Ibiza

MADE IN  
SPAIN

 **ideal**  
TILE & STONE

## ABOUT


---

Ibiza is a colorful and bold collection of white-body ceramic tiles with a straight edge, designed for those seeking visual impact and a sophisticated aesthetic. Available in 10 colors with a high shade variation, Ibiza offers versatility and a modern style in any environment. Each color stands out with its glossy finish, which brings luminosity, depth, and character to any space. In a 2x16 format with a coordinating .5x8 jolly, Ibiza is ideal for creative applications in kitchens, bathrooms, living rooms and more.







## Suggested Applications



## Installation Suggestions



## Tile Type



## Shade Variation



## Slip Resistance

DCOF	Values	Applications
	0.42	Recommended Standard DCOF value for wet/dry commercial flooring
	0.65	Recommended Standard DCOF value for ADA ramps

DIN 51130 \*R9: Industry Standard/ADA Requirements \*\*R11: Recommended For Exteriors

R9\* (3-10°)  R10 (10-19°)  R11\*\* (19-27°)  
 R12 (27-35°)  R13 (>35°)

ASTM C-1028  
ANSI A137.1  
DIN 51097/51130

### DIN 51097

Class	Typical Applications	Critical Angle
<input type="checkbox"/> A	Barefoot, but mainly dry aisles and walkways, dry changing areas	≥12°
<input type="checkbox"/> B	Shower rooms, pool surrounds, wet changing areas, disinfectant spray areas (plus all Class A areas)	≥18°
<input type="checkbox"/> C	Areas constantly under water, e.g. steps into pools, foot baths, included pool surrounds, jacuzzis (plus all Class A&B areas)	≥24°

## Scratch Resistance

MOH'S SCALE  
UNI EN ISO  
10545.6

### MINERAL

- |                            |                                   |
|----------------------------|-----------------------------------|
| 1. Talc (Talc)             | 6. Microline (Glass, Glazed Tile) |
| 2. Gypsum (Fingernail)     | 7. Quartz (Unglazed Porcelain)    |
| 3. Calcite (Penny)         | 8. Topaz (Granite)                |
| 4. Fluorite (Some Marbles) | 9. Corundum (Ruby)                |
| 5. Apatite (Knife Blade)   | 10. Diamond (Diamond)             |
- Industry standard ≤175mm²

## Wear Resistance

PEI RATING  
UNI EN ISO  
10545.7

- Class 1: Walls only
  - Class 2: Residential floors w/minimal abrasive traffic
  - Class 3: Residential interiors/light commercial traffic
  - Class 4: Medium commercial applications
  - Class 5: All commercial applications/heavy traffic
- \*Wear can vary greatly. please consult with a professional.*

## Stain Resistance

ASTM C1378-04  
UNI EN ISO  
10545.14

- 5: Removed after 5 minutes (hot water running)
- 4: Removed by manual cleaning (weak detergent)
- 3: Removed by mechanical cleaning (strong detergent)
- 2: Removed by immersion (24 hrs in suitable solvent)
- 1: Stain not removed

## Water Absorption

ASTM C-373  
UNI EN ISO  
10545.3

Absorbs 0-.5%  Absorbs .5-3%  Absorbs 3-7%  Absorbs 7% +

**Impervious** Interior/Exterior Frost Resistant  
**Vitreous** Interior/Exterior Frost Resistant  
**Semi-Vitreous** Indoor Use Only  
**Non-Vitreous** Indoor Use Only

## Breaking Strength

ASTM C648  
UNI EN ISO  
10545.4

Industry standard should be greater than 250 lbs or 50 N/MM²

## Facial Dimension

ASTM c499-09  
UNI EN ISO  
10545.02

Standard	Tolerance	Result
flatness	±5mm	±.5% <b>PASS</b>
thickness	±6mm	±.5% <b>PASS</b>
straightness	±4.5mm	±.5% <b>PASS</b>
squareness	±5.4mm	±.6% <b>PASS</b>
sides L/W	±1.1mm / ±4.5mm	±.5% <b>PASS</b>

## Chemical Resistance

ASTM C650  
UNI EN ISO  
10545.13

Allowances for:

	result
Acid	<b>GLA</b>
Bases	<b>GHB</b>
Chemicals	<b>GA</b>

## Lead Information



REQUIREMENTS FOR COMMERCIAL INTERIORS/NEW CONSTRUCTION

Sustainable Sites	1 Point
Site selection	
SS CREDIT 1 Heat Island Effect-non roof Material with a solar reflectant index of at least 29.	<input type="checkbox"/>
Energy & Atmosphere	1 Point
EA CREDIT 4 Green Power: Products that optimize energy performance for floors and walls using thermal conductivity. BTU-FT	<input type="checkbox"/>
Indoor Environmental Quality	1 Point
Low-Emitting Materials-Flooring Systems	
IEQ CREDIT 3.1-7 Green Cleaning: Reducing occupants exposure to hazardous cleaning chemicals.	<input type="checkbox"/>
IEQ CREDIT 4.1 Low Emitting Adhesives: Products less than 65 G/L VOC	<input type="checkbox"/>
IEQ CREDIT 4.3 Low Emitting Materials: Flooring systems.	<input type="checkbox"/>

Materials & Resources	1 Point	2 Points
M&R CREDIT 2 Construction Waste Management: Recycling salvaged construction waste in to new reusable materials.	50% <input type="checkbox"/>	70% <input type="checkbox"/>
M&R CREDIT 4.1-4.2 Recycled Content: The sum of post consumer plus 1/2 of the pre consumer reps at least 10-20% of total value of materials.	10% <input type="checkbox"/>	20% <input type="checkbox"/>
M&R CREDIT 5 Regional Materials: Materials manufactured within 500 miles of the project site.	10% <input type="checkbox"/>	20% <input type="checkbox"/>
Innovation in Design	1-5 Points	
ID CREDIT 1 Innovation in Design Measurable exemplary environmental performance.	<input type="checkbox"/>	

Type: **Ceramic Tile**

Product Line: **Ibiza**

*\*The marketing name for this product is property of IDEAL Tile & Stone. This same product may be marketed under different names.\**